



Section	Wy	ly	Width	Height	Thickness	Weight	Coating area	
		cm ³ /m	cm ⁴ /m	mm	mm	mm	kg/m ¹	m ² /m
VKZ 471-5	471	5.421	809	230	5,0	40,0	49,4	2,22
VKZ 617-5	617	8.338	766	270	5,0	40,0	52,2	2,35
VKZ 644-5	644	9.785	766	304	5,0	40,0	52,2	2,35
VKZ 784-5	784	13.136	722	355	5,0	40,0	55,4	2,49
VKZ 965-5	965	20.516	676	425	5,0	40,0	59,2	2,66
VKZ 699-6	699	9.611	792	275	6,0	48,0	62,7	2,27
VKZ 783-6	783	11.939	748	305	6,0	48,0	64,1	2,41
VKZ 878-6	878	14.265	725	325	6,0	48,0	66,2	2,48
VKZ 1153-6	1.153	21.741	655	377	6,0	48,0	73,2	2,75
VKZ 1167-6	1.167	23.626	659	405	6,0	48,0	72,8	2,73
VKZ 1246-6	1.246	29.280	903	470	6,0	60,0	66,4	2,55
VKZ 491-7	491	4.293	794	175	7,0	56,0	70,5	2,27
VKZ 532-7	532	4.923	787	185	7,0	56,0	71,1	2,29
VKZ 846-7	846	11.628	737	275	7,0	56,0	75,9	2,44
VKZ 921-7	921	14.095	727	306	7,0	56,0	77,0	2,48
VKZ 1078-7	1.078	17.790	694	330	7,0	56,0	80,6	2,59
VKZ 1257-7	1.257	24.517	665	390	7,0	56,0	84,3	2,71
VKZ 1330-7	1.330	25.130	644	378	7,0	56,0	86,9	2,80
VKZ 1201-8	1.201	19.820	685	330	8,0	64,0	93,4	2,63
VKZ 1227-8	1.227	20.865	683	335	8,0	64,0	93,6	2,64
VKZ 1257-8	1.257	22.000	679	350	8,0	64,0	94,3	2,65
VKZ 1481-8	1.481	28.008	639	378	8,0	64,0	100,1	2,82
VKZ 1244-9	1.244	19.527	700	314	9,0	72,0	102,9	2,57
VKZ 1307-9	1.307	20.908	686	320	9,0	72,0	105,0	2,62
VKZ 1684-9	1.684	31.568	630	375	9,0	72,0	114,3	2,86
VKZ 1735-9	1.735	34.270	627	395	9,0	72,0	114,7	2,87
VKZ 1771-9	1.771	39.857	882	450	9,0	90,0	102,0	2,61
VKZ 1832-9	1.832	41.228	871	450	9,0	90,0	103,3	2,64
VKZ 1349-10	1.349	20.567	682	305	10,0	80,0	117,2	2,64
VKZ 1404-10	1.404	22.468	677	320	10,0	80,0	118,1	2,66
VKZ 1720-10	1.720	30.964	636	360	10,0	80,0	125,7	2,83
VKZ 1929-10	1.929	36.648	607	380	10,0	80,0	131,7	2,97
VKZ 2354-10	2.354	55.898	808	475	10,0	100,0	123,8	2,85
VKZ 2468-10	2.468	61.702	795	500	10,0	100,0	125,8	2,89
VKZ 2628-10	2.628	70.289	776	535	10,0	100,0	128,9	2,96
VKZ 3082-10	3.082	88.594	715	575	10,0	100,0	139,8	3,22

Manufactured in accordance with:
 Technical delivery conditions in accordance with EN 10249-1.
 Tolerances in accordance with EN 10249-2.

Steel qualities:
 S 235, S 275, S 355 or Equivalent with 3.1 Certificate in accordance with EN 10204.

Standard availability:
 Lengths up to 24.000 mm, longer lengths on request.



Alternatives for AZ-Profiles:

IBZ 5-850	656	11.160	850	340	5,0	42,8	50,4
IBZ 6-800	638	9.505	800	300	6,0	48,5	62,0
IBZ 7-850	714	12.034	850	340	6,0	51,3	60,6
IBZ 7-725	730	10.727	725	300	6,0	45,0	60,4
IBZ 8-725	846	11.540	725	271	7,0	52,0	71,7
IBZ 12-770	1.245	21.430	770	344	8,5	72,6	94,0
IBZ 12-850	1.205	24.651	850	420	7,0	44,3	75,3
IBZ 13-770	1.300	22.360	770	344	9,0	76,1	99,0
IBZ 13-850	1.318	26.360	850	400	8,0	73,1	86,0
IBZ 14-770	1.355	23.300	770	345	9,5	79,5	103,0
IBZ 17-700	1.730	36.330	700	420	8,5	73,1	104,4
IBZ 18-700	1.800	37.800	700	420	9,0	76,5	109,0
IBZ 18-850	1.805	43.335	850	480	9,0	85,9	101,1
IBZ 19-750	1.944	44.718	750	460	9,0	80,9	107,8
IBZ 20-700	1.945	40.950	700	421	10,0	83,3	119,0
IBZ 20-850	2.000	46.862	850	470	10,0	96,0	112,9
IBZ 24-700	2.430	55.768	700	459	11,2	95,7	136,7
IBZ 26-700	2.600	59.800	700	460	12,2	102,9	147,0
IBZ 28-700	2.760	63.620	700	440	13,2	110,0	157,0
IBZ 28-725	2.800	75.965	725	550	10,0	94,9	130,9
IBZ 33-700	3.285	82.929	700	500	12,0	76,7	163,0
IBZ 36-700	3.600	89.668	700	520	12,5	118,6	169,4
IBZ 37-700	3.710	92.415	700	499	12,5	124,5	177,8
IBZ 39-700	3.905	97.500	700	560	13,5	133,0	190,0
IBZ 42-750	4.231	116.350	750	550	13,0	141,6	188,8
IBZ 46-580	4.600	110.465	580	540	15,0	133,0	229,0
IBZ 48-750	4.805	124.921	750	520	15,0	172,4	229,8
IBZ 50-580	5.020	121.070	580	580	16,0	146,8	253,0